



TECHNICAL DATA SHEET

SAMAN WOOD PUTTIES : WP-XXXX SERIES

DESCRIPTION

Saman wood putty is used to repair cracks, holes and imperfections on wood surfaces: hardwood, softwood, chipboard, plywood, etc. It is easy to apply, adheres well, dries quickly and sand easily. It does not shrink, sink or crack.

PRODUCT SPECIFICATIONS

pH: 8.0-8.5

Solids: 75 ± 1 % (by weight); 56 ± 1 % (by volume)

Viscosity: thick paste

Density: 1.7-1.8 kg/l

Drying times: approximately 30 minutes for a thin layer at 70°F and 50% relative humidity. Drying time is dependent upon temperature, humidity and thickness of application

Coverage: 60-80 sq. ft/liter

VOC: <50 g/l

Recommended applicators: spatula

Clean up: Clean applicator and equipment with water.

Storage: Store in a cool, dry place. Keep from freezing.

Shelf life: at least 1 year in a well closed container.

APPLICATION

Surface preparation

Surfaces must be clean, dry and free of wax, grease, oil and mildew.

Finish application

1. Saman wood putty is ready to use. If necessary, mix the product before starting the application.
2. Apply the wood putty with a spatula larger than the cracks or holes to fill and level it well. For deep holes, repeat the application.
3. Allow to dry and remove the excess with sandpaper to obtain a smooth surface.
4. Apply a wood finish on the repaired surface.

To the best of our knowledge, the information contained herein is accurate. Since conditions and methods are beyond our control, no warranty is expressed or implied as for the final result. The user is advised to access the suitability of the product on a test area before application.