



Safety Data Sheet

Exterior translucent finish

1. Identification

Product identifier: Exterior translucent finish
Product code: TPO-020, TPO-025, TPO-040
Supplier Name: SamaN
660 Rue du Filtre
Victoriaville, Québec
G6T 0T6
Telephone: 819 751-2350
Emergency telephone number: 819-751-2350
Available hours: 8h-17h

Recommended use: Exterior coating for bare wood
Restrictions on use: For outdoor use only

2. Hazard identification

Hazard classification: DANGER

Product classification:



Self-heating substances and mixtures-Category 1. Flammable liquids-Category 4.
Germ cell mutagenicity-Category 1B. Carcinogenicity-Category 1B.
Skin sensitization-Category 1.

Hazard statement(s): Self-heating; may catch fire. Combustible liquid. May cause an allergic skin reaction. May cause genetic defects. May cause cancer.

Precautionary statement(s)

Prevention: Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Keep away from heat/sparks/open flames/hot surfaces – No smoking. Wear protective gloves, protective clothing, eye and face protection. Avoid breathing mist, vapours, and spray. Keep cool. Contaminated work clothing should not be allowed out of the workplace.



Safety Data Sheet

Exterior translucent finish

Response: IF ON SKIN: Wash with plenty of water and soap. If skin irritation or a rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: use an appropriate extinguisher.

Disposal: Store in a well ventilated place. Maintain air gap between stacks/pallets. Store bulk masses greater than 450 kg/1000 lbs at temperatures not exceeding 25°C/77°F. Store away from other materials. Store locked up.

Storage: Dispose of contents/container in accordance with local, regional, national and/or international regulations in force.

Other hazards: No other effects shown.

See toxicological information, section 11

3. Composition/Information on ingredients

No	CAS no	Common name and synonyms	Concentration (W/W)
1	64742-47-8	Naphtha hydrotreated (light fraction)	14.73%
2	64742-88-7	Naphtha (medium aliphatic fraction C9-C12)	2.67%
3	96-29-7	Methyl ethyl ketoxime	0.70%
4	8052-41-3	Stoddard solvent	0.53%
5	41556-26-7	BIS(1,2,2,6,6-pentamethyl-4-piperidiny) sebacate	0.29%
6	1333-86-4	Carbon black, (C.I. pigment black 7)	0.17%



Safety Data Sheet

Exterior translucent finish

4. First-aid measures

If swallowed, irritation, any type of overexposure or symptoms of overexposure occur during use of the product or persists after use, immediately contact a POISON CENTER, an EMERGENCY ROOM or a PHYSICIAN; ensure that the product safety data sheet is available.

Eye contact: Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.

Skin contact: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.

Inhalation: Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.

Ingestion: Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Symptoms: Skin hypersensitivity. Diarrhea. Cough, breathing pain, eye redness and skin edema.

Effects (acute or delayed): May cause skin sensitization. Laxative effect, if ingested in large quantities. May cause irritation of eyes, skin and respiratory tract.

Immediate medical attention and special treatment: No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.



Safety Data Sheet

Exterior translucent finish

5. Fire-fighting measures

Suitable extinguishing media: Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media: Jets of water can facilitate the spread of fire.

Specific hazards arising from the hazardous product: Combustible. If heated, vapors may form explosive mixtures with air. The vapors are heavier than air and may travel to an ignition source.

Hazardous combustion products: Carbon monoxide and dioxide.

Special protective equipment and precautions for fire-fighters: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

Protective equipment and emergency procedures: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosionproof equipment. Dispose of via a licensed waste disposal contractor.



Safety Data Sheet

Exterior translucent finish

7. Handling and storage

Precautions for safe handling: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Avoid exposure - obtain special instructions before use. Avoid contact with eyes, skin and clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

Conditions for safe storage: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Incompatibility: Chlorinated products. Strong oxidizing agents.

8. Exposure controls/Personal protection

No	CAS no	CAS name	IDHL mg/m3	TWA mg/m3	STEL mg/m3	CEIL mg/m3
1	64742-47-8	Naphtha hydrotreated (light fraction)	Not available	Not available	Not available	Not available
2	64742-88-7	Naphtha (medium aliphatic fraction C9-C12)	Not available	Not available	Not available	Not available
3	96-29-7	Methyl ethyl ketoxime	Not available	Not available	Not available	Not available
4	8052-41-3	Stoddard solvent	20000	525	Not available	Not available
5	41556-26-7	BIS(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	Not available	Not available	Not available	Not available
6	1333-86-4	Carbon black, (C.I. pigment black 7)	1750	3.5	Not available	Not available

IDHL: Immediately Dangerous to Life or Health Concentrations

TWA : Time Weighted Average

STEL: Short -Term Exposure Limit

CEIL: Ceiling Limit



Safety Data Sheet

Exterior translucent finish

IPVS = Inmediatamente peligroso para la vida o la salud

VEPP = Valor de exposición promedio ponderado

VECD = valor de exposición de corta duración

VL = valor límite

Appropriate engineering controls: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eyes: DO NOT WEAR CONTACT LENSES Wear anti-splash safety goggles.

Hands: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties.

Respiratory: If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Others: Wear protective clothing with long sleeves and appropriate safety shoes at all times.

9. Physical and chemical properties

Physical state: Liquid

Colour: Translucent

Odour: Low odor

Odour threshold: Not available

pH: Not applicable

Melting/Freezing point: -32°C (-25.6°F)

Initial boiling point/boiling range: 178°C (352.4°F)

Flash point: 79°C (174.2°F) Close cup

Lower flammable/explosive limit: 0,6% at 25 °C

Upper flammable/explosive limit: 7% at 25 °C

Auto-ignition temperature: 285°C (545°F)

Evaporation rate: <1 (ether=1)



Safety Data Sheet

Exterior translucent finish

Vapour pressure: Not available

Vapour density: < 1 (air =1)

Relative density: 0,935-0,937 kg/L à 20 °C (water = 1)

Solubility in water: Insoluble

Partition coefficient - n-octanol/water: Not available

Decomposition temperature: Not available

Kinematic viscosity: 50,4 mm²/s (à 40 °C)

10. Stability and reactivity

Reactivity: Stable under recommended conditions of storage and handling. It reacts strongly with oxidizing materials, to release gas and heat. The product is unstable in pure form.

Chemical stability: The product is chemically stable under normal conditions of use.

Possibility of hazardous reactions: Danger of explosion when heated. Materials such as rags used with this product may begin to burn by themselves.

Conditions to avoid: Keep away from sources of ignition, open flames and sparks, Avoid electrical discharge. Do not pierce or burn, even after use.

Incompatible materials: This product can attack certain types of plastic, rubber or coatings.

Hazardous decomposition products: Carbon monoxide and dioxide.

11. Toxicological information

No	CAS no	CAS name	(1) LD oral	(2) LD skin	(3) LD skin	(4) LC gases	(5) LC vapours	(6) LC dusts-mist
1	64742-47-8	Naphtha hydrotreated (light fraction)	>5000	Not available	>2000	Not applicable	>20,00	>5,00
2	64742-88-7	Naphtha (medium aliphatic fraction C9-C12)	Not available	Not available	Not available	Not applicable	>20,00	>5,00
3	96-29-7	Methyl ethyl ketoxime	2326	Not available	1000	Not applicable	>20,00	>5,00
4	8052-41-3	Stoddard solvent	>5000	Not available	>3000	Not applicable	>20,00	>5,50
5	41556-26-7	BIS(1,2,2,6,6-pentamethyl-4-piperidiny) sebacate	Not available	Not available	Not available	Not applicable	>20,00	>5,00



Safety Data Sheet

Exterior translucent finish

6	1333-86-4	Carbon black, (C.I. pigment black 7)	>8000	Not available	>3000	Not applicable	Not applicable	>5,00
---	-----------	--------------------------------------	-------	---------------	-------	----------------	----------------	-------

- (1) LD₅₀ oral mg/kg
- (2) LD₅₀ skin mg/kg
- (3) LD₅₀ skin mg/kg
- (4) LC₅₀ inhalation ppmV 4h gases
- (5) LC₅₀ inhalation mg/l 4h vapours
- (6) LC₅₀ inhalation mg/l 4h dusts-mist

Routes of exposure: This product is absorbed through the respiratory tract, skin and gastrointestinal tract.

Symptoms: Skin hypersensitivity. Diarrhea. Cough, breathing pain, eye redness and skin edema.

Delayed and immediate effects: May cause skin sensitization. Laxative effect, if ingested in large quantities. May cause irritation of eyes, skin and respiratory tract.

No	CAS no	CAS name	IARC	ACGIH	Mutagenicity	Effect on reproduction
1	64742-47-8	Naphtha hydrotreated (light fraction)	Not available	Not available	Not available.	Not available.
2	64742-88-7	Naphtha (medium aliphatic fraction C9-C12)	Not available	Not available	No effects shown.	Not available.
3	96-29-7	Methyl ethyl ketoxime	2B	A3	Not available.	Not available.
4	8052-41-3	Stoddard solvent	3	A4	The data do not allow for an adequate assessment of mutagenic effects.	No effects shown.
5	41556-26-7	BIS(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	Not available	Not available	Not available.	Not available.
6	1333-86-4	Carbon black, (C.I. pigment black 7)	2B	A3	Mutagenic effects shown in animals or suspected in humans.	Not available.

Cancer classification under IARC (International Agency for Research on Cancer)

Group 1: carcinogenic to humans.



Safety Data Sheet

Exterior translucent finish

- Group 2A: probably carcinogenic to humans.
- Group 2B: possibly carcinogenic to humans.
- Group 3: not classifiable as to its carcinogenicity to humans.
- Group 4: probably not carcinogenic to humans.

Cancer classification under ACGIH (American Conference of Governmental Industrial Hygienists)

- Group A1: confirmed human carcinogen.
- Group A2: suspected human carcinogen.
- Group A3: confirmed animal carcinogen with unknown relevance to humans.
- Group A4: not classifiable as a human carcinogen.
- Group A5: not suspected as a human carcinogen.

12. Ecological information

No	CAS no	CAS name	%	Persistent	Bio-accumulation	Aquatic ecotoxicity
1	64742-47-8	Naphtha hydrotreated (light fraction)	14.73	No	Yes	Yes
2	64742-88-7	Naphtha (medium aliphatic fraction C9-C12)	2.67	No	Yes	Yes
3	96-29-7	Methyl ethyl ketoxime	0.70	Yes	No	No
4	8052-41-3	Stoddard solvent	0.53	No	Yes	Yes
5	41556-26-7	BIS(1,2,2,6,6-pentamethyl-4-piperidiny) sebacate	0.29	Yes	Yes	Yes
6	1333-86-4	Carbon black, (C.I. pigment black 7)	0.17	Yes	No	No

No	CAS no	CAS name	%	Ecotoxicity for aquatic organisms-Short term	Ecotoxicity for aquatic organisms-Long term	Environnemental effects
1	64742-47-8	Naphtha hydrotreated (light fraction)	14.73	No known adverse effect to aquatic life.	No known adverse effect to aquatic life.	No known adverse effect to the environment.
2	64742-88-7	Naphtha (medium aliphatic fraction C9-C12)	2.67	No known adverse effect to aquatic life.	No known adverse effect to aquatic life.	No known adverse effect to the environment.
3	96-29-7	Methyl ethyl ketoxime	0.70	No known adverse effect to aquatic life.	No known adverse effect to aquatic life.	No known adverse effect to the environment.
4	8052-41-3	Stoddard solvent	0.53	No known adverse effect to aquatic life.	No known adverse effect to aquatic life.	No known adverse effect to the environment.



Safety Data Sheet

Exterior translucent finish

5	41556-26-7	BIS(1,2,2,6,6-pentamethyl-4-piperidiny) sebacate	0.29	Very toxic to aquatic life.	Very toxic to aquatic life with long lasting effects.	No known adverse effect to the environment.
6	1333-86-4	Carbon black, (C.I. pigment black 7)	0.17	No known adverse effect to aquatic life.	No known adverse effect to aquatic life.	No known adverse effect to the environment.

13. Disposal considerations

Methods of disposal: The generation of waste should be avoided or minimized wherever possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally.

14. Transport information

	TDG	DOT	IMDG	IATA
UN number				
Proper shipping name				
Transport hazard class(es)				
Packing group				

Other information

Marine pollutant: No

IMDG: Not applicable

Exemption for limited quantity: Not applicable

Special precautions: Not applicable

Others exemptions: Not applicable



Safety Data Sheet

Exterior translucent finish

15. Regulatory information

Canada

No	CAS	CAS name	%	DSL	NSL	NPRI
1	1333-86-4	Carbon black, (C.I. pigment black 7)	0.17	X		
2	41556-26-7	BIS(1,2,2,6,6-pentamethyl-4-piperidiny) sebacate	0.29	X		
3	8052-41-3	Stoddard solvent	0.53	X		X
4	96-29-7	Methyl ethyl ketoxime	0.70	X		X
5	64742-88-7	Naphtha (medium aliphatic fraction C9-C12)	2.67	X		X
6	64742-47-8	Naphtha hydrotreated (light fraction)	14.73	X		X

United-States

No	No CAS	Nom CAS	%	TSCA	PROP-65	Right to Know
1	1333-86-4	Carbon black, (C.I. pigment black 7)	0.17	X	X	X
2	41556-26-7	BIS(1,2,2,6,6-pentamethyl-4-piperidiny) sebacate	0.29	X		
3	8052-41-3	Stoddard solvent	0.53	X		X
4	96-29-7	Methyl ethyl ketoxime	0.70	X		
5	64742-88-7	Naphtha (medium aliphatic fraction C9-C12)	2.67	X		
6	64742-47-8	Naphtha hydrotreated (light fraction)	14.73	X		

All ingredients are listed on the EINECS or in compliance with the inventory.

The customer is responsible for determining the PPE (personal protection equipment) code for this material.

The classification of the product and the SDS were developed in accordance with HPR.

16. Other information

Date: 2017-12-12

Version: 1

Notice to the reader: The manufacturer hereby declares that the information disclosed herein have been based on governmental sites and/or raw material suppliers'. The manufacturer has no control over the nature and content of such information. The manufacturer fully reproduces all the information it holds on the constituent of the product, at the time it is manufactured. The manufacturer does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. By this data sheet, the manufacturer hereby discloses all the potential dangers it has knowledge of and which might be related to the using or manipulation of the product in order to allow the proper care to be brought and use with regard to the product. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist and notification is hereby given to the user. Notice is hereby given that injury can derive therefrom if the foregoing is not respected. The manufacturer assumes no responsibility for personal and/or material damage, lost or injury of whichever nature caused or which may occur following the wrongful, inappropriate, negligent or abusive use or handling of the product or from not having read the herein contained information.